



Product Service

# Attestation of Conformity

No. N8A 076729 0114 Rev. 24

**Holder of Attestation:** **Seraphim Solar System Co.,Ltd.**

No.1-2, Hengyao Rd, Henglin Zhen  
Wujin District  
213101 Changzhou  
PEOPLE'S REPUBLIC OF CHINA

**Product:** **Crystalline Silicon Terrestrial Photovoltaic (PV) Modules**  
**Mono-crystalline Silicon Photovoltaic Module**

This Attestation of Conformity is issued on a voluntary basis according to the Low Voltage Directive 2014/35/EU relating to electrical equipment designed for use within certain voltage limits. It confirms that the listed equipment complies with the principal protection requirements of the directive and is based on the technical specifications applicable at the time of issuance. It refers only to the particular sample submitted for conformity assessment. For details see: [www.tuvsud.com/ps-cert](http://www.tuvsud.com/ps-cert)

**Test report no.:** 704061801207-30

**Date,** 2023-06-02

( Zhulin Zhang )

Page 1 of 3

This Attestation does not replace the regulatory EU Declaration of Conformity (DoC) and does not allow for CE marking. After preparation of the necessary documentation and establishing compliance to requirements of all applicable directives, the manufacturer may sign a DoC and apply the CE marking. The DoC is issued under the sole responsibility of the manufacturer.



TUV®



Product Service

# Attestation of Conformity

No. N8A 076729 0114 Rev. 24

## Model(s):

1500 V DC Maximum System voltage,  
Fire Safety Class C Modules:  
SRP-xxx-6MA-HV (xxx=330-400, in step of 5);  
SRP-xxx-6MB-HV (xxx=275-330, in step of 5);  
SRP-xxx-E01A-HV (xxx=365-420, in step of 5);  
SRP-xxx-E01B-HV (xxx=305-350, in step of 5);  
SRP-xxx-BMA-HV (xxx=330-455 and xxx=525-560, in step of 5);  
SRP-xxx-BMB-HV  
(xxx=275-380 and xxx=440-465 and xxx=590-610, in step of 5);  
SRP-xxx-BMC-HV  
(xxx=305-380 and xxx=485-510 and xxx=650-675, in step of 5);  
SRP-xxx-BMD-HV (xxx=390-420 and xxx=535-550, in step of 5);  
SRP-xxx-BME-HV (xxx=475-490, in step of 5);  
SRP-xxx-BMF-HV (xxx=415-430, in step of 5);  
SRP-xxx-E6A-HV (xxx=410-435, in step of 5);  
SRP-xxx-E6B-HV (xxx=350-370, in step of 5);  
SRP-xxx-BMZ-HV (xxx=425-450 and xxx=565-605 in step of 5);  
SRP-xxx-6MA-TB (xxx=330-400, in step of 5);  
SRP-xxx-6MB-TB (xxx=275-330, in step of 5);  
SRP-xxx-E01A-TB (xxx=365-420, in step of 5);  
SRP-xxx-E01B-TB (xxx=305-350, in step of 5);  
SRP-xxx-BMA-TB (xxx=330-455 and xxx=525-560, in step of 5);  
SRP-xxx-BMB-TB  
(xxx=275-380 and xxx=440-465 and xxx=590-610, in step of 5);  
SRP-xxx-BMC-TB  
(xxx=305-380 and xxx=485-510 and xxx=650-675, in step of 5);  
SRP-xxx-BMD-TB (xxx=390-420 and xxx=535-550, in step of 5);  
SRP-xxx-BME-TB (xxx=475-490, in step of 5);  
SRP-xxx-BMF-TB (xxx=415-430, in step of 5);  
SRP-xxx-E6A-TB (xxx=410-435, in step of 5);  
SRP-xxx-E6B-TB (xxx=350-370, in step of 5);  
SRP-xxx-BMZ-TB (xxx=425-450 and xxx=565-605 in step of 5);  
SRP-xxx-TM72-HV (xxx=530-555, in step of 5);  
SRP-xxx-TM68-HV (xxx=500-520, in step of 5);  
SRP-xxx-TM64-HV (xxx=475-490, in step of 5);  
SRP-xxx-TM60-HV (xxx=445-460, in step of 5);  
SRP-xxx-TM56-HV (xxx=415-430, in step of 5);  
SRP-xxx-TM52-HV (xxx=385-400, in step of 5);  
SRP-xxx-TM48-HV (xxx=355-370, in step of 5);  
SRP-xxx-BTA-HV (xxx=550-590, in step of 5);  
SRP-xxx-BTB-HV (xxx=460-490, in step of 5);  
SRP-xxx-BTC-HV (xxx=505-540, in step of 5);  
SRP-xxx-BTD-HV (xxx=415-440, in step of 5);  
SRP-xxx-BTZ-HV (xxx=595-625, in step of 5);

1000 V DC Maximum System voltage,  
Fire Safety Class C Modules:  
SRP-xxx-6MA (xxx=330-400, in step of 5);  
SRP-xxx-6MB (xxx=275-330, in step of 5);  
SRP-xxx-E01A (xxx=365-420, in step of 5);  
SRP-xxx-E01B (xxx=305-350, in step of 5);  
SRP-xxx-BMA (xxx=330-455 and xxx=525-560, in step of 5);  
SRP-xxx-BMB  
(xxx=275-380 and xxx=440-465 and xxx=590-610, in step of 5);  
SRP-xxx-BMC  
(xxx=305-380 and xxx=485-510 and xxx=650-675, in step of 5);  
SRP-xxx-BMD (xxx=390-420 and xxx=535-550, in step of 5);  
SRP-xxx-BME (xxx=475-490, in step of 5);  
SRP-xxx-BMF (xxx=415-430, in step of 5);  
SRP-xxx-E6A (xxx=410-435, in step of 5);  
SRP-xxx-E6B (xxx=350-370, in step of 5);

Page 2 of 3

This Attestation does not replace the regulatory EU Declaration of Conformity (DoC) and does not allow for CE marking. After preparation of the necessary documentation and establishing compliance to requirements of all applicable directives, the manufacturer may sign a DoC and apply the CE marking. The DoC is issued under the sole responsibility of the manufacturer.





Product Service

# Attestation of Conformity

No. N8A 076729 0114 Rev. 24

SRP-xxx-BMZ (xxx=425-450 and xxx=565-605 in step of 5);

1500 V DC Maximum System voltage,

Fire Safety Class A Modules:

SRP-xxx-6MA-BG (xxx=350-395, in step of 5);

SRP-xxx-6MB-BG (xxx=295-325, in step of 5);

SRP-xxx-6MA-DG (xxx=350-395, in step of 5);

SRP-xxx-6MB-DG (xxx=295-325, in step of 5);

SRP-xxx-BMA-BG (xxx=330-455 and xxx=525-560, in step of 5);

SRP-xxx-BMB-BG

(xxx=290-380 and xxx=440-465 and xxx=590-610, in step of 5);

SRP-xxx-BMC-BG

(xxx=320-375 and xxx=485-510 and xxx=650-675, in step of 5);

SRP-xxx-BMD-BG (xxx=395-420 and xxx=535-545, in step of 5);

SRP-xxx-BME-BG (xxx=475-490, in step of 5);

SRP-xxx-BMF-BG (xxx=415-430, in step of 5);

SRP-xxx-BMA-DG (xxx=350-425, in step of 5);

SRP-xxx-BMB-DG (xxx=290-350, in step of 5);

SRP-xxx-BMC-DG (xxx=320-350, in step of 5);

SRP-xxx-BMZ-BG (xxx=425-450 and xxx=565-605 in step of 5);

SRP-xxx-TM72-BG (xxx=530-555, in step of 5);

SRP-xxx-TM68-BG (xxx=500-520, in step of 5);

SRP-xxx-TM64-BG (xxx=475-490, in step of 5);

SRP-xxx-TM60-BG (xxx=445-460, in step of 5);

SRP-xxx-TM56-BG (xxx=415-430, in step of 5);

SRP-xxx-TM52-BG (xxx=385-400, in step of 5);

SRP-xxx-TM48-BG (xxx=355-370, in step of 5);

SRP-xxx-BTA-BG (xxx=550-590, in step of 5);

SRP-xxx-BTB-BG (xxx=460-490, in step of 5);

SRP-xxx-BTC-BG (xxx=505-540, in step of 5);

SRP-xxx-BTD-BG (xxx=415-440, in step of 5);

SRP-xxx-BTZ-BG (xxx=595-625, in step of 5).

xxx is standing for rated output power at STC.

## Parameters:

Safety Class:	Class II
Max. System Voltage:	1000V DC or 1500V DC
Test Laboratory:	Changzhou HuaYang Inspection and Testing Technology Co., Ltd No.8 Lanxiang Road Wujin Economic Development Zone Changzhou, Jiangsu, China.
Construction:	Framed or Frameless, with Junction box, cable and connector.
Fire Safety Class:	Class C or Class A according to UL790

## Tested according to:

EN IEC 61730-1:2018  
EN IEC 61730-1:2018/AC:2018-06  
EN IEC 61730-2:2018  
EN IEC 61730-2:2018/AC:2018-06

Page 3 of 3

This Attestation does not replace the regulatory EU Declaration of Conformity (DoC) and does not allow for CE marking. After preparation of the necessary documentation and establishing compliance to requirements of all applicable directives, the manufacturer may sign a DoC and apply the CE marking. The DoC is issued under the sole responsibility of the manufacturer.

